CSB-620L
Ceiling Speaker







Key features:

Superb sounding bass reflex loaded indoor rimless ceiling-mount speaker for a wide range of commercial audio applications, including conference rooms, cafes, restaurants, seminar rooms, training rooms which require high quality speech and background audio playback.

- 6.5” 2-way bass reflex ceiling mounted passive speaker
- Slim front grille – Only 8mm thick
- Strong N42 Neodymium Magnet for front grille
- Shallow depth back enclosure box
- Superb frequency response with nice aesthetics design.
- Designed for a wide range of applications, including: Conferences, Retail stores, Hospitality venues, Restaurants & bars, Places of worship, Performing arts venues.

Technical specification		
Acoustic design	2-way Bass reflex loading	
Drive units	1x 6.5” LF 1 x 1” dome HF	
Power rating	80W continuous, 160W peak	
Frequency response	65Hz to 20KHz	
Nominal impedance	8Ω	
Sensitivity	90 dB/m/W	
Maximum SPL	Continuous : 105dB SPL / Peak: 108dB SPL	
Connectors	Lockable Phoenix connector	
Installation	Ceiling mount with front connection	
Dimension	Embedded depth Cutout diameter Speaker outer diameter Panel/board thickness requirement	175mm 280mm 326mm 10-50mm
Weight	4.4kg	
Back Enclosure Material	Metal	