Theater Series

Model: TS-6PR





Key features:

Weather resistant 2-way speaker designed for clarity and bass extension. Suitable for indoor and outdoor wall-mount installations. Consists of a 6.5 inch woofer, 1 inch tweeter and twin 5.25 inch passive radiators for a full frequency response in a compact reinforced polypropylene enclosure.

- All weather, 6.5” 2-way wall mounted passive speaker
- Smooth frequency response with bass extension
- Low-impedance (8Ω) / high-impedance (70V/100V)
- Superb sound with esthetic design, no DSP or EQ required.
- Designed for a wide range of applications, including: Conference centers, Retail stores, Hospitality venues, Restaurangs & bars, Places of worship, Performing arts venus.

Technical specification	
Acoustic design	Closed box with twin passive radiators
Drive units	1x 1” HF 1x 6.5” LF 2x 5.25” Passive radiators
Power rating	@ 8Ω Low Impedance : 40W continuous @ 100V High impedance : 40W/ 20W/10W
Crossover	2.5KHz
Frequency response	50Hz to 20KHz
Nominal impedance	8 ohms
Sensitivity	87 dB/m/W
Maximum SPL	Continuous : 102dB SPL / Peak: 104dB SPL
Connectors	Spring loaded binding posts
Installation	Surface mounted vertical or horizontal
Dimension with side bracket	(L)320 x (W)220 x (D)152 mm
Weight	4.4kg
Accessories included	U-Bracket